



Main

Range of product	TeSys B
Product or component type	Contacteur
Device short name	LC1BP
Contacteur application	Motor-heating-lighting
Utilisation category	AC-1 AC-3
Control circuit type	AC
Coil type	Standard
Poles description	3P
Pole contact composition	3 NO
[In] rated current	1500 A ≤ 55 °C AC AC-3 power circuit 2000 A ≤ 40 °C AC AC-1 power circuit
Motor power kW	425 kW 220...230 V AC 50/60 Hz 670 kW 1000 V AC 50/60 Hz 700 kW 500 V AC 50/60 Hz 750 kW 380...400 V AC 50/60 Hz 750 kW 660...690 V AC 50/60 Hz 800 kW 415 V AC 50/60 Hz 800 kW 440 V AC 50/60 Hz
Control circuit voltage	110 V AC 50...400 Hz

Complementary

Auxiliary contact composition	2 NO + 2 NC
Control circuit voltage limits	0.35...0.5 U _c drop-out 50...400 Hz 0.85...1.1 U _c operational 50...400 Hz
[Ui] rated insulation voltage	1000 V IEC 60158-1 power circuit 1000 V IEC 60947-4 power circuit 1500 V VDE 0110 group C power circuit
Mounting mode	Fixed
Mounting support	Bar support bracket Notched mounting rails
Connections - terminals	Bars power circuit 3 100 x 5 mm
Tightening torque	35 N.m power circuit bars
[U _e] rated operational voltage	≤ 1000 V AC 50/60 Hz power circuit
[I _{th}] conventional free air thermal current	2000 A ≤ 40 °C power circuit
I _{rms} rated making capacity	15000 A 1000 V AC power circuit IEC 60947-4 15000 A 1000 V AC power circuit IEC 60158-1
Rated breaking capacity	5000 A 1000 V power circuit IEC 60158-1 5000 A 1000 V power circuit IEC 60947-4 9000 A 660...690 V power circuit IEC 60158-1 9000 A 660...690 V power circuit IEC 60947-4 12000 A 500 V power circuit IEC 60158-1 12000 A 500 V power circuit IEC 60947-4 15000 A 440 V power circuit IEC 60947-4 15000 A 440 V power circuit IEC 60158-1
Associated fuse rating	1600 A aM ≤ 440 V power circuit 2000 A gI ≤ 440 V power circuit
Average impedance	0,13 mOhm 50 Hz 2000 A power circuit
Power dissipation per pole	290 W AC-3 2000 A 520 W AC-1 2000 A
Inrush power in VA	1300 VA 50/60 Hz
Hold-in power consumption in VA	31 VA 50/60 Hz

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Operating time	50...100 ms opening 100...150 ms closing
Mechanical durability	1200000 cycles
Operating rate	120 cyc/h \leq 55 °C
Height	490 mm
Width	790 mm
Depth	475 mm
Product weight	94 kg

Environment

Standards	BS 5424 IEC 60158-1 IEC 60947-4 NF C 63-110 VDE 0660
Product certifications	BV CSA RINA
Protective treatment	TC TH
Ambient air temperature for operation	-5...55 °C
Ambient air temperature for storage	-60...80 °C
Operating altitude	3000 m without
RoHS EUR conformity date	4Q2008
RoHS EUR status	Will not be compliant